



Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations			
2	FireMastic-300™ - 50mm Wide x 25mm Deep PE Backing Rod Masonry		ndary Fire Stopping Product ary Fire Stopping Product	100mm Thick	FRL -/120/60	Up to 50mm Wide Gap				
								Sales & Technical	1300 502 677	
								International	+61 2 9531 8597	1
								Web	bossfire.com	
								Drawing Information:		
		Secondary Fire Stopping Product						Category 1	Wall	
		PE Backing Rod						Category 2	Linear Gap Seal	
				LIMITATION				Category 3	-	
				BOSS Passive Fire Pty Ltd has p		chnical information in good faith and to the best of its knowledge. of publication. Should any data come to BOSS Passive Fire of the product described, BOSS Passive Fire Pty Ltd reserve the ve Fire strive to constantly improve and develop products so this as a guide only and it does not constitute a guarantee of lication may have specific requirements and you should and understood the appropriate certification relative to your		Test Standard	AS1530.4:2014/AS4072.1-2005 Branz FAR 3821	
		Tertiary Fire Stopping Product		attention relating to the fire resista	ance or performance of			Test Reference		
				information may change without r	notice.			Drawing Number	W-LG-008	
				compliance of all applications. Ea	ich project and/or applic			Product DWG ID	FM3-030	
				needs, and ensure you seek acce	tance from the Certifyir	ing Authority or compliance inspector before ins contact BOSS Technical Services. +61 2 9531	ore installation. For 2 9531 8591	Drawn By	EG	Rev 01
				Copyright © 2020 BOSS Passive				Date of Issue	08/02/2022	