



								Trans.		
Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations			
	Fire Rated Plasterboard (Min Single Layer PB), Concrete & Masonry FireMastic-HPE™ - Nominal Depth 13mm Paircoil - 9.52mm / 6.35mm TPS Power Cable - 2C+E 1.5mm² Data Cable 16mm PVC Flexible Outlet Pipe Foam Backing Rod	FireMastic-HPE™	Fire Rated Plasterboard (Min Single Layer PB), Concrete & Masonry	Min 90mm Thick	-/60/60		one side of wall only		B I V E	FIRE
3 4 5 6								Sales & Technical	1300 502 677	
								International	+61 2 9531 85	91
								Web	bossfire.com	
								Drawing Information:		
		Secondary Fire Stopping Product						Category 1	Wall	
								Category 2	Service Penetr	ation
								Category 3	PairCoil	
				BOSS Fire & Safety Pty Ltd has	ovided the above technical information in good faith and to the correct at the time of publication. Should any data come to			Test Standard	AS1530.4-2014/AS4072.1	
		Tertiary Fire Stopping Product	attention relating to the fire resistance or performance of the product described, BOSS Fire & Safety Pty Ltd reserve the right to amend this document or drawing. BOSS Fire & Safety strive to constantly improve and develop products so this				Test Reference	CSIRO COT2918		
			information may change without notice. The information contained herein has been developed as a guide only and it does not constitute a guarantee of					Drawing Number	Number W-SP-PCL-004	
								Product DWG ID	ct DWG ID HPE-011	
								Drawn By	EG	Rev 04
				Copyright © 2020 BOSS Fire & S				Date of Issue	14/09/2020	· · · · · · · · · · · · · · · · · · ·

