



Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations		066
3 4	Fire Rated Plasterboard, Concrete & Masonry MaxiCollar™ 32mm FireMastic-HPE™ - Nominal Depth of MaxiCollar™ Plasterboard Screw 25mm Up to 32mm PP-R Pipe (Aquatherm)	MaxiCollar™ 32mm Fin	Fire Rated Plasterboard, Concrete & Masonry	Min 118mm Thick	provided the above technic be correct at the time of put tance or performance of the drawing. BOSS Fire & Safo notice.  In has been developed as an ach project and/or application that you have read and septance from the Certifying Fire® certification please co	hnical information in good faith and to the b f publication. Should any data come to BO's f the product described, BOSS Fire & Safet Safety strive to constantly improve and dev is a guide only and it does not constitute a cation may have specific requirements and ind understood the appropriate certification ying Authority or compliance inspector before e contact BOSS Technical Services. +61 2	20mm Pipe 38mm Aperture for 32mm Pipe  best of its knowledge. OSS Fire & Safety's fety Pty Ltd reserve the evelop products so this a guarantee of nd you should n relative to your fore installation. For 2 9531 8591		S I V E F I R E
								Sales & Technical	1300 502 677
								International	+61 2 9531 8591
								Web	bossfire.com
								Drawing Information:	
								Category 1	Wall
		FireMastic-HPE™ (Infill) 25mm Depth of Collar						Category 2	Service Penetration
								Category 3	Plastic Pipes
				BOSS Fire & Safety Pty Ltd has				Test Standard	AS1530.4-2014/AS4072.1
		Tertiary Fire Stopping Product		attention relating to the fire resista					FRT180403b.1
				information may change without				Drawing Number	W-SP-PLS-006
				compliance of all applications. Ea				Product DWG ID	MC-005
				needs, and ensure you seek acc				Drawn By	EG Rev 03
				Copyright © 2020 BOSS Fire & S				Date of Issue	14/09/2020
								1	