



Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations		2000
3 4 5	16mm & 6mm Paircoil with 13mm thick lagging FireMastic-HPE™ - 25mm deep Comflor® 60 BOSS Batt Mechanical Fixing with Washer 25mm uPVCPipe (33.6mm OD)	FireMastic-HPE™ - 25mm deep	Comflor® 60 - Composite Floor System	Min 75mm Profile	FRL -/120/120	16mm & 6mm Paircoil with 13mm thick lagging + 25mm uPVCPipe (33.6mm OD)			S S I V E F I R E
								Sales & Technical	1300 502 677
								International	+61 2 9531 8591
								Web	bossfire.com
								Drawing Information:	
		Secondary Fire Stopping Product						Category 1	Floor
		BOSS Batt						Category 2	Service Penetration
								Category 3	Paircoil Bundles
				BOSS Fire & Safety Pty Ltd has p		d the above technical information in good faith and to the best of its le ect at the time of publication. Should any data come to BOSS Fire &		Test Standard	AS1530.4:2014/AS4072.1-2005
		Tertiary Fire Stopping Product		attention relating to the fire resista	ance or performance of	or performance of the product described, BOSS Fire & Safeing. BOSS Fire & Safety strive to constantly improve and dev	ety Pty Ltd reserve the velop products so this	Test Reference	RIR FRT 180137.2
				information may change without r	notice.			Drawing Number	F-SP-PCL-007
				compliance of all applications. Ea	ch project and/or appli	roject and/or application may have specific requirements and tyou have read and understood the appropriate certification		Product DWG ID	HPE-028
				needs, and ensure you seek acceptance from the Certifying Authority or compliance inspector updates on the range of BOSS Fire® certification please contact BOSS Technical Services. +			pefore installation. For	Drawn By	EG Rev 03
				Copyright © 2020 BOSS Fire & S				Date of Issue	24/08/2021