



				,					
Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations		nee
2 3	22 x TPS Cables 2C+E 2.5mm² FireMastic-HPE™ - 25mm deep Comflor® 60	FireMastic-HPE™ - 25mm deep	Comflor® 60 - Composite Floor System	Min 75mm Profile	FRL -/120/120	ded the above technical information in good faith and to the b prrect at the time of publication. Should any data come to BOS or performance of the product described, BOSS Fire & Safet ing. BOSS Fire & Safety strive to constantly improve and deve	e best of its knowledge. OSS Fire & Safetys fety Pty Ltd reserve the evelop products so this	PAS	SIVE FIRE
	BOSS Batt Mechanical Fixing with Washer							Sales & Technical	1300 502 677
	The state of the s							International	+61 2 9531 8591
								Web	bossfire.com
								Drawing Information:	
		Secondary Fire Stopping Product						Category 1	Floor
		BOSS Batt						Category 2	Service Penetration
								Category 3	Power Cables
				BOSS Fire & Safety Pty Ltd has p	be correct at the time of			100t Otanidara	AS1530.4:2014/AS4072.1-2005
		Tertiary Fire Stopping Product		attention relating to the fire resista	ance or performance of			Test Reference	RIR FRT 180137.2
				information may change without n	notice.			Drawing Number	F-SP-POW-021
				compliance of all applications. Each project and/or application may have specific requirer investigate these carefully. Ensure that you have read and understood the appropriate of			nts and you should	Product DWG ID	HPE-027
				needs, and ensure you seek acce	eptance from the Certify	in the Certifying Authority or compliance inspector before ation please contact BOSS Technical Services. +61.2	efore installation. For	Drawn By	EG Rev 02
				Copyright © 2020 BOSS Fire & Sa				Date of Issue	24/08/2021
					_				