



OTHER APPLICABLE SUBSTRATES				
PLASTERBOARD	MASONRY	CONCRETE	ACC/HEBEL	SPEEDPANEL

Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations
1 2 3 4 5	Wall (See Applicable Substrates) PenoPatch™ 60mm 12mm Nails or Screws depending on substrate 5 x CAT6 Data Cables 3 x CAT6 Data Cables	PenoPatch™ 60mm	<b>Min 118mm Thick Walls:</b> -FR Plasterboard / GIB -Concrete -Masonry -AAC / Hebel  <b>Walls with Build Up to Min 118mm:</b> -Speedpanel & Korok -AAC / Hebel  <b>Build up options - 100mm clearance from perimeter of service:</b> -BOSS Batt -FR Plasterboard (Edge to be sealed with 20mm deep sealant)	118mm	-/60/30 -/60/60	Aperture 20mm Dia 5 x CAT6 Data Cables (-/60/30) 3 x CAT6 Data Cables (-/60/60) with wrapped PenoPatch	In masonry / concrete wall PenoPatch to be fixed using two masonry nails (min 12mm long). In AAC / Hebel, Speedpanel & Korok wall PenoPatch to be fixed using two metal screws (min 12mm long).
		<b>Secondary Fire Stopping Product</b>					
		<b>Tertiary Fire Stopping Product</b>					
				<p><b>LIMITATION</b> BOSS Fire &amp; Safety Pty Ltd has provided the above technical information in good faith and to the best of its knowledge. This information was deemed to be correct at the time of publication. Should any data come to BOSS Fire &amp; Safety's attention relating to the fire resistance or performance of the product described, BOSS Fire &amp; Safety Pty Ltd reserve the right to amend this document or drawing. BOSS Fire &amp; Safety strive to constantly improve and develop products so this information may change without notice.</p> <p>The information contained herein has been developed as a guide only and it does not constitute a guarantee of compliance of all applications. Each project and/or application may have specific requirements and you should investigate these carefully. Ensure that you have read and understood the appropriate certification relative to your needs, and ensure you seek acceptance from the Certifying Authority or compliance inspector before installation. For updates on the range of BOSS Fire® certification please contact BOSS Technical Services. +61 2 9531 8591 Copyright © 2020 BOSS Fire &amp; Safety Pty Ltd. All rights reserved.</p>			

<b>Sales &amp; Technical</b>	1300 502 677		
<b>International</b>	+61 2 9531 8591		
<b>Web</b>	bossfire.com		
<b>Drawing Information:</b>			
<b>Category 1</b>	Wall		
<b>Category 2</b>	Service Penetration		
<b>Category 3</b>	Data Cables		
<b>Test Standard</b>	AS1530.4: 2014/AS4072.1-2005		
<b>Test Reference</b>	FAS 190100		
<b>Drawing Number</b>	W-SP-DAT-010		
<b>Product DWG ID</b>	PP-003		
<b>Drawn By</b>	EG	<b>Rev</b>	05
<b>Date of Issue</b>	01/07/2021		