



Component Schedule	Component Name	Primary Fire Stopping Product	Applicable Substrates	Min Substrate Thickness (If Applicable)	Applicable FRL	Service Specifications	Limitations		06	
1 2 3	Fire Rated Plasterboard, ACC, Concrete & Masonry FireMastic-HPE™ - Nominal Depth 25mm Copper Pipe 15mm Dia - Continuously lagged with 13mm thick Armaflex Insulation	FireMastic-HPE™	Fire Rated Plasterboard, ACC, Concrete & Masonry	Min 120mm Thick	-/120/120	Copper Pipe 15mm Dia - Continuously lagged with 13mm thick Armaflex Insulation	Apperture to suit 20mm wide annular gap around service	P A S	S I V E	F I R E
								Sales & Technical	1300 502 677	
								International	+61 2 9531 859	)1
								Web	bossfire.com	
								Drawing Information:		
		Secondary Fire Stopping Product						Category 1	Wall	
								Category 2	Service Penetra	ation
				LIMITATION				Category 3	Insulated Metal Pipes	
				BOSS Fire & Safety Pty Ltd has provided the above technical information in good faith and to the best of its knowledge. This information was deemed to be correct at the time of publication. Should any data come to BOSS Fire & Safety's attention relating to the fire resistance or performance of the product described, BOSS Fire & Safety Pty Ltd reserve the right to amend this document or drawing. BOSS Fire & Safety strive to constantly improve and develop products so this information may change without notice.  The information contained herein has been developed as a guide only and it does not constitute a guarantee of compliance of all applications. Each project and/or application may have specific requirements and you should investigate these carefully. Ensure that you have read and understood the appropriate certification relative to your needs, and ensure you seek acceptance from the Certifying Authority or compliance inspector before installation. For updates on the range of BOSS Fire® certification please contact BOSS Technical Services. +61 2 9531 8591 Copyright © 2020 BOSS Fire & Safety Pty Ltd. All rights reserved.			Test Standard	AS1530.4-2014/AS4072.1		
		Tertiary Fire Stopping Product					fety Pty Ltd reserve the	Test Reference	CSIRO-2990B W-SP-IMT-001	
							• •	Drawing Number		
							Product DWG ID	HPE-019		
							Drawn By	EG	Rev 02	
							2 9031 8091	Date of Issue	14/09/2020	'
L	I	I							1	