

# SAFETY DATA SHEET

## SECTION 1: PRODUCT AND COMPANY INFORMATION

**PRODUCT NAME:** ABLATIVE COATING™

**PRODUCT FORM:** Sealant

**PRESCRIBED USE:** Fire Rated Coating for sealing bulkhead batts and penetrations.

**COMPANY/SUPPLIER:** Boss Passive Fire Pty Ltd

**ADDRESS:** Unit 1, 16 Atkinson Road, Taren Point, NSW. 2229

**TELEPHONE:** 02 95318591

**EMERGENCY TELEPHONE:** 1300 502 677

**EMAIL:** [info@bossfire.com.au](mailto:info@bossfire.com.au)

This SDS is provided by SHARP and HOWELLS Pty Ltd (Consulting Chemists).

WEBSITE: [www.sharpandhowells.com.au](http://www.sharpandhowells.com.au)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the Mixture

GHS-US classification (Globally Harmonised System of Classification and Labelling of Chemicals (GHS))

Aspiration Hazard, Category 2.	H305
Skin Corrosion/irritation, Category 2	H315
Sensitization, Skin Category 1, 1A, 1B	H317
Serious eye damage/eye irritation, Category 2A	H319
Specific Target Organ toxicity, single exposure, Respiratory Tract Irritation, Category 3,	H335
Hazardous to aquatic environments, Long Term Hazard, Category 3	H412

### 2.2 Label Elements

GHS-US labelling

Hazard Pictograms:



Signal Word:

Warning

Hazard Statements:

H305 – May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 – May cause an allergic skin reaction.  
H319- Causes serious eye irritation  
H335 – May cause respiratory irritation  
H412 – Harmful to aquatic life with long lasting effects

Precautionary Statements:

P203- Obtain, read and follow all safety instructions before use.  
P261 – Avoid breathing fumes/gas/mist/vapours/spray/dust  
P264 - Wash hands thoroughly after handling  
P265 – Do not touch eyes  
P271 – Use outdoors or in well ventilated area.  
P273- Avoid release to the environment  
P280- Wear eye protection, protective clothing, protective gloves

Response Statements:

P301 + P316 - **IF SWALLOWED**: Get emergency medical help immediately.  
P331 – Do NOT induce vomiting  
P302 + P352- **IF ON SKIN**, wash with plenty of water.  
P332 + P317 – If skin irritation occurs get medical help.  
P362 + P364- Remove contaminated clothing and wash before reuse.  
P305 + P354 +P338 – **IF IN EYES**: Immediately rinse with water for several minutes.  
Remove contact lenses if present band easy to do so. Continue rinsing.  
P317 – Get emergency medical help.  
P304 + P340 - **IF VAPOURS INHALED** Remove person to fresh air and keep comfortable for breathing.  
P319 – Get medical help if you feel unwell.

Storage Requirements:

P403 + P233 – Store in well ventilated space. Keep container tightly closed

Disposal Requirements:

P501: Dispose of contents/container in accordance with the relevant regulations.

### 2.3 Other Hazards

No other information available

### **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

<b><u>Chemical Entity</u></b>	<b><u>CAS No.</u></b>	<b><u>Proportion</u></b>
Calcium Carbonate	1317-65-3	20 - 60 %
Aluminium Hydroxide	21645-51-2	1 - 10 %
Acrylic Polymers	-	10 - 40%
Hydrocarbons (Petroleum)	-	< 5 %
Sodium Hydroxide	1310-73-2	< 1%
Isothiazolones, mixed	26172-55-4	< 1 %
Other ingredients (deemed non-hazardous.)	-	Balance

### **SECTION 4: FIRST AID MEASURES**

#### **Inhalation:**

Vapours may cause irritation of the throat and/or tightness in the chest.  
Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

#### **Ingestion:**

Ingestion may cause irritation to mouth or throat. Wash mouth out with water.  
Seek immediate medical assistance if you feel unwell.  
May be fatal if ingested material enters airways. Do not induce vomiting. Get emergency medical help immediately

#### **Skin Contact:**

May cause irritation and redness at contact site. Wash off skin thoroughly with water. Shower if necessary. Seek medical attention for persistent irritation of the skin.

#### **Eye Contact:**

May causes irritation and redness. Flush thoroughly with flowing water for 15 minutes to remove all traces. Remove contact lenses if present and easy to do so. Get specialist medical attention.

### **SECTION 5: FIRE FIGHTING MEASURES**

**Suitable Extinguishing Media:** Extinguishing media suitable for surrounding fire should be used.

**Hazardous Combustion Products:** Toxic fumes are likely to be emitted during combustion.

**Protective Equipment & Precautions for Firefighters:** Wear self-contained breathing apparatus and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin and eyes
<b>Environmental Precautions:</b>	Should not be released into the environment Advise emergency services and appropriate local environment authority if contamination occurs.
<b>Cleaning up and Containment:</b>	Wash the spillage site with large quantities of water. Soak up with inert absorbent. Notify authorities if product enters sewers or public waters. Dispose of solid residues at an authorised site. Keep in suitable sealed containers for disposal.

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling:

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### Conditions for safe storage.

Store in a cool, dry, well-ventilated area. Keep container tightly closed.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Standards:

<u>Chemical Entity</u>	<u>Reference</u>	<u>TWA (mg/m<sup>3</sup>)</u>	<u>STEL(mg/m<sup>3</sup>)</u>
Calcium Carbonate	SafeWork Australia	10 mg/m <sup>3</sup>	
Aluminium Hydroxide	WEL (UK)	10mg/m <sup>3</sup>	4 mg/m <sup>3</sup>
Sodium Hydroxide	NIOSH (USA)	2mg/m <sup>3</sup>	
Other Ingredients	No exposure Limits available		

### Engineering Controls:

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment.

#### **Respiratory protection:**

If insufficient ventilation, use a NIOSH/MSHA approved respirator.

#### **Skin protection:**

Wear standard duty gloves (AS 2161: *Industrial safety gloves and mittens*), loose comfortable clothing, and boots. Long-sleeved shirts and long trousers are recommended.

#### **Eye protection:**

Non-fogging chemical resistant safety goggles, glasses (AS/NZS 1336: *Recommended practices for eye protection in the occupational environment*)

**Personal protective equipment symbols.**



**Hygiene measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the toilet and at the end of the working period.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State:</b>	Paste
<b>Appearance:</b>	White
<b>Odour:</b>	Slight
<b>Density:</b>	1.5 g/cm <sup>3</sup>
<b>Viscosity:</b>	Highly Viscous.
<b>Boiling Point &amp; Boiling Range:</b>	Data unavailable
<b>Flash Point:</b>	> 200 °C
<b>Evaporation Rate:</b>	Slow
<b>Flammability:</b>	Not Flammable
<b>Upper/Lower Flammability/Explosive Limits:</b>	Data unavailable
<b>Vapour pressure:</b>	Data unavailable
<b>Vapour density:</b>	Data unavailable
<b>Water Solubility:</b>	Miscible with water
<b>pH (1% solution)</b>	8.8
<b>Partition Coefficient:</b>	Data unavailable
<b>Auto-Ignition Temperature:</b>	Data unavailable

**SECTION 10: STABILITY AND REACTIVITY**

<b>Stability:</b>	Product is stable under normal conditions of use, storage and transport.
<b>Reactivity:</b>	Product is non-reactive under normal conditions of use, storage and transport.
<b>Conditions to avoid:</b>	None, under recommended storage and handling conditions
<b>Incompatible Materials:</b>	Strong Acids, Strong Oxidizing Agents.
<b>Hazardous Decomposition Products:</b>	None, under normal conditions of storage and use.
<b>Hazardous Reactions:</b>	None known under normal conditions of use.

## SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity (oral) : Not classified  
 Acute Toxicity (dermal) : Not classified  
 Acute Toxicity (inhalation) : Not classified

Component	LD50 Oral Rat	LD50 Dermal	LD50 Inhalation -Rat
Aluminium Hydroxide	LD50 >2000mg/kg bodyweight	Not Listed	LD50= >2.3 mg/l air

Component	LD50 Oral Rat	LD50 Dermal	LC50 Inhalation -Rat
Calcium Carbonate	LD50 = 6450 mg/kg ( Rat )	> 2000 mg/kg (Rat) (OECD Guideline 402)	> 3 mg/L 4h (Rat) (OECD Guideline 403)

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation - Rat
2-Methyl-3-isothiazolone	LD50 232 - 249 mg/kg ( Rat )	LD50 = 200 mg/kg ( Rabbit )	LD50 = 0.11 mg/L ( Rat ) 4 h

**Toxicologically Synergistic :** No information available

**Irritation:** No information available

**Sensitization:** No information available

**Carcinogenicity:** No information available

**Mutagenic Effects:** No information available

**Reproductive Effects:** No information available

**Developmental Effects:** No information available

**Teratogenicity:** No information available

**STOT – Single exposure:** None known

**STOT-repeated exposure:** None known

**Aspirational hazard:** No information available

**Endocrine disruptor Information:** No information available

**Symptoms after inhalation:** Vapours may cause irritation of the throat and/or tightness in the chest.

**Symptoms after skin contact:** Mild skin irritation with itching and redness at point of contact

**Symptoms after eye contact:** Contact with eyes may cause severe eye irritation, severe pain, cause eyes to water profusely, cause vision to become blurred, and may cause permanent eye damage.

**Symptoms after ingestion:** Ingestion may result in soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Other Adverse effects:** The toxicological properties have not been fully investigated

## **SECTION 12: ECOLOGICAL INFORMATION**

<b>Toxicity:</b>	Ecology General: - Harmful to aquatic Life with long lasting effects Hazardous to aquatic environment - short term -acute (Not classified) Hazardous to aquatic environment - long term -chronic: Harmful to aquatic life with long lasting effects
<b>Persistence &amp; Degradability:</b>	Biodegradable, Not persistent in the environment.
<b>Bioaccumulation/Accumulation:</b>	No Bioaccumulation Potential
<b>Mobility:</b>	Water miscible so likely to be mobile.
<b>Other information:</b>	Avoid release into the environment

## **SECTION 13: DISPOSAL CONSIDERATIONS**

<b>Disposal Recommendations:</b>	Dispose of in compliance with federal, provincial, state, territory and local requirements.
<b>Special precautions:</b>	Avoid release to the environment

## **SECTION 14: TRANSPORT INFORMATION**

<b><u>DOT.</u></b>	Not Regulated
<b><u>IATA.</u></b>	Not Regulated
<b><u>IMDG/IMO</u></b>	Not Regulated
<b><u>TDG</u></b>	Not Regulated
<b><u>ADG</u></b>	Not Regulated

Not classified as hazardous for transport by road, rail, sea or air

## **SECTION 15: REGULATORY INFORMATION**

**National Regulations.**  
Contains no AICS (Australian Inventory of Chemical Substances) restrictions

## **SECTION 16: OTHER INFORMATION**

**Creation Date: June 2022**  
**Version: 1.00**  
**Due for revision: June 2027**

### **Key to abbreviations:**

ACGIH	American Conference of Governmental Industrial Hygienists
ADG	Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS	Australian Inventory of Chemical Substances
ASCC	Australian Safety and Compensation Council
CAS	Chemical Abstracts Service Registry Number
DOT	Department of Transportation (USA)

GHS	Globally Harmonised System of Classification and Labelling of Chemicals
HSIS	Hazardous Substances Information System
ICAO	International Civil Aviation Organisation
IOELV	Indicative Occupational Exposure Limit Value (European Union)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Organisation Rules
NTP	National Toxicity Program (USA)
OSHA	Occupational Safety & Health Administration (USA)
STEL	Short term exposure limit
TWA	Time weighted average
TDG	Transportation of Dangerous Goods Act (Canada)
REACH	EU Regulation - acronym for the Registration, Evaluation, Authorization and Restriction of Chemicals.
WEL	Workplace Exposure Limit (United Kingdom)
LC <sub>Lo</sub>	Lethal Concentration Low – lowest concentration causing death
LD <sub>Lo</sub>	Lethal Dose Low – lowest dose causing death
LC <sub>50</sub>	Lethal Concentration required to kill 50% of test population
EC <sub>50</sub>	Half maximal effective concentration

////////////////////////////////////

**This SDS has been prepared and issued by:**

**Sharp and Howells Pty Ltd**  
**Chartered Chemists**  
**41 Greenaway Street, Bulleen, Victoria, 3105, Australia.**  
**Phone: (03) 9850 9722**  
**Fax: (03) 9850 9733**

*The information contained herein is based on the present state of our knowledge. This document characterises the product with regard to the appropriate safety precautions, and is only proposed as a guide when applied for its intended use. Each intended user should consult this SDS, and perform their own appropriate risk assessment in context to how the product will be handled and used in the workplace. Sharp and Howells Pty Ltd will not be responsible for any loss or damages resulting from use of or reliance on the information and advice contained herein.*



www.potters.co.nz  
 0800 POTTERS | info@potters.co.nz  
 Auckland, Wellington + Christchurch