
















THERMATEX[®] Fissura

Features

- THERMATEX Fissura ceilings provide good acoustical performance
- Fine perforated surface
- High light reflective finish (LR 0.84)
- Available in a range of edge profiles and sizes
- Ideal for offices, libraries and classrooms



THERMATEX Fissura

	Panel Options	Board	Tegular 24																
 Edge details																			
 Dimensions (mm)	600 x 600 x 16mm	805333	805335																
	1200 x 600 x 16mm	805334	805339																
1. Special items and other sizes available upon request. 2. For all items: Contact your local AMF Distributor representative for stock availability.																			
 Suspension systems	24mm Grid																		
 Weight	4.0 kg/m ²																		
 Colour	White																		
 Sound absorption	<table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>NRC</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_P</td> <td>0.60</td> <td>0.45</td> <td>0.40</td> <td>0.50</td> <td>0.70</td> <td>0.70</td> <td>0.65</td> </tr> </tbody> </table> <p>NRC = 0.60 as per EN ISO 354 & EN ISO 11654</p>		Frequency f (Hz)	NRC	125	250	500	1000	2000	4000	α_P	0.60	0.45	0.40	0.50	0.70	0.70	0.65	 <p>α_p</p> <p>125 250 500 1000 2000 4000</p> <p>* NRC = 0.60</p>
Frequency f (Hz)	NRC	125	250	500	1000	2000	4000												
α_P	0.60	0.45	0.40	0.50	0.70	0.70	0.65												
 Sound attenuation	EN ISO 10848-2 CAC = 600x600mm = 33 dB, 1200x600mm = 34 dB as per EN ISO 717-1																		
 Fire resistance	Conforms with NCC Spec. C1.10 as tested to AS 5637.1:2015 - Group 1, and ISO 5660 - Group 1 - S																		
 Light reflectance	84%																		
 Thermal resistance	R-Value = 0.40 m ² K/W as per EN 12667																		
 Humidity resistance	Maximum 49°C/95% RH																		
 Cleanability	Wipeable																		

Specifications

- Ceiling system shall comprise AMF Thermatex Fissura.
- Panels shall achieve NRC 0.60, CAC 33-34.
- Nominal size 600x600x16mm / 1200x600x16mm with Board edge / Tegular 24 edge.
- Suspension system shall be 24mm Grid.



POTTER
INTERIOR SYSTEMS

Distributed by

www.potters.co.nz

0800 POTTERS. | info@potters.co.nz

Auckland, Hamilton, Wellington + Christchurch

