

THERMATEX® Alpha ONE



THERMATEX® Alpha ONE is a new wet-felt mineral tile which provides highest sound absorption values. With a strong white acoustic fleece THERMATEX® Alpha ONE offers a smooth, elegant surface finish. The combination of bio-soluble mineral wool with clay and starch provides excellent physical characteristics.

SYSTEM

Exposed Grid System, demountable ceiling

Dimensions

600 × 600 mm
1200 × 1200 mm

Please note

Additional sizes available on request

Thickness / Weight


24 mm (approx. 4.0 kg/m²)

Colour

White similar to RAL 9010

Edge details

SK, VT24



Additional edge details available on reques

TECHNICAL PERFORMANCE

Building material class A2-s1, d0 as per EN 13501-1

Fire resistance F30 - F90 as per DIN 4102 part 2 (as per test certificate)
REI30 - REI90 per EN 13501 part 2 (as per test certificate)

Sound absorption EN ISO 354

 α_{W} = 1.00 as per EN ISO 11654 NRC = 1.00 as per ASTM C 423

Sound attenuation D_{n,f,w} = 29 dB as per EN ISO 10848 (24 mm thickness, according to test report)

Light reflectance for white similar to RAL 9010 glare-free approx. 88%

Thermal conductivity $\lambda = 0.040 \text{ W/mK}$ as per EN 12667

Air permeability PM1 (≤ 30 m³/hm²) as per DIN 18177

Humidity up to 95% RH


Clean room classification class 4 as per ISO 14644-1

Interior air Indoor air comfort GOLD status





Knauf AMF GmbH & Co. KG
Elsenthal 15
D-94481 Grafenau Germany
Telefon 08552 / 422-0 - Fax 08552 / 422-32
info@knaufamf.de - www.knaufamf.com



Due to reproduction processes colours shown in this catalogue may differ from the actual product colour. Product selection should always be made from AMF samples. All details and technical information stated in this brochure or other publicity material referring to AMF ceiling systems are based on test reports obtained under laboratory conditions. It is the responsibility of the customer to ensure that this data is suitable for the proposed application. All information provided is based on current technical data. Further relevant test reports, assessments and installation guidelines are available. All system details conform with current standards and are based on the use of AMF products and system components. AMF accepts no liability or responsibility for use of third party components, or for any variations to conditions stipulated in test data. Mixing of production batches is not recommended. All technical data is subject to change without prior notice and is governed by AMF Terms and Conditions of Sales. This catalogue supersedes all previous editions. Errors and omissions excepted. Printing errors excepted.

