

## THERMATEX® Thermaclean

## Features

- THERMATEX Thermaclean combines excellent cleanability with good resistance to germs and fungi. It has a laminated finish with a white vinyl foil, that ensures a timeless look
- Good sound attenuation (34 dB)
- ISO 4
- Ideal for healthcare environments, laboratories, treatment rooms, intensive care units



## **THERMATEX**<sup>®</sup> Thermaclean

		Panel Options	Board	
→	Edge details			
			24mm Grid	
;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;	Dimensions (mm)	1200 x 600 x 15mm	123257	
	Suspension systems	24mm Grid		
	Weight	3.6 kg/m <sup>2</sup>		
	Colour	White		
	Sound absorption		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	
<b>at</b>	Sound attenuation	EN ISO 10848-2 CAC = 36 dB as per ASTM E 413-10		
<b>S</b>	Fire resistance	Euroclass A2-s3, d0 as per EN 13501-1		
	Light reflectance	81%		
ļ	Thermal conductivity	$\lambda$ = 0.060 m <sup>2</sup> K/W as per EN 12667		
	Humidity resistance	RH95		
++	Clean room	ISO 4 as per ISO 14644-1		
(+	Indoor air quality	A+ E1	Cleanability / Durability	
	Sustainability	45%		



## **Distributed by**

www.potters.co.nz 0800 POTTERS. | info@potters.co.nz Auckland, Hamilton, Wellington + Christchurch

