


























# THERMATEX<sup>®</sup> Thermaclean

## Features

- THERMATEX Thermaclean combines excellent cleanability with good resistance to germs and fungi. It has a laminated finish with a white vinyl foil, that ensures a timeless look
- Good sound attenuation (34 dB)
- ISO 4
- Ideal for healthcare environments, laboratories, treatment rooms, intensive care units



# THERMATEX® Thermaclean

	Panel Options	Board														
 <b>Edge details</b>		 Prelude 24mm Grid														
 <b>Dimensions (mm)</b>	1200 x 600 x 15mm	123257														
 <b>Suspension systems</b>	Shall be AMF: Prelude 24mm steel T-Bar															
 <b>Weight</b>	3.6 kg/m <sup>2</sup>															
 <b>Colour</b>	White															
 <b>Sound absorption</b>	<table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td><math>\alpha_P</math></td> <td>0.35</td> <td>0.20</td> <td>0.10</td> <td>0.10</td> <td>0.10</td> <td>0.10</td> </tr> </tbody> </table> <p>NRC = 0.15 as per ASTM C 423</p>	Frequency f (Hz)	125	250	500	1000	2000	4000	$\alpha_P$	0.35	0.20	0.10	0.10	0.10	0.10	 <p>• NRC = 0.15</p>
Frequency f (Hz)	125	250	500	1000	2000	4000										
$\alpha_P$	0.35	0.20	0.10	0.10	0.10	0.10										
 <b>Sound attenuation</b>	EN ISO 10848-2 CAC = 36 dB as per ASTM E 413-10															
 <b>Fire resistance</b>	Euroclass A2-s3, d0 as per EN 13501-1															
 <b>Light reflectance</b>	81%															
 <b>Thermal conductivity</b>	$\lambda = 0.060 \text{ m}^2\text{K/W}$ as per EN 12667															
 <b>Humidity resistance</b>	RH95															
 <b>Clean room</b>	ISO 4 as per ISO 14644-1															
 <b>Indoor air quality</b>	 A+  E1	<b>Cleanability / Durability</b>   														
<b>Sustainability</b>	 45%  															



**POTTER**  
INTERIOR SYSTEMS

Distributed by

[www.potters.co.nz](http://www.potters.co.nz)

0800 POTTERS. | [info@potters.co.nz](mailto:info@potters.co.nz)

Auckland, Hamilton, Wellington + Christchurch

