

## THERMATEX® Alpha HD

		Panel Options	Board	Tegular 24/90
<u>→</u>	Edge details			
			24mm Grid	24mm Grid
mm (111 1112)	Dimensions (mm)	600 x 600 x 24mm	207197	207200
		1200 x 600 x 24mm	228134	220966
	Suspension systems	24mm Grid		
<b>Λ</b> κg \	Weight	4.0kg/m <sup>2</sup>		
	Colour	White		
<b>*</b>	Sound absorption	Thickness         NRC         125           24mm         1.00         0.55           NRC = 1.00 as per ASTM	250 500 1000 2000 4000 H 0.85 1.00 0.95 1.00 1.00 α C 423 & EN ISO 354	
<b>*</b>	Sound attenuation	EN ISO 10848-2 CAC 30 dB (19mm) as per EN ISO 717-1		
<b>F</b>	Fire resistance	Conforms with NCC Spec. C1.10 as tested to AS 5637.1:2015 - Group 1, and ISO 5660 - Group 1 - S		
<b>///</b>	Light reflectance	88%		
	Thermal conductivity	λ = 0.40 m <sup>2</sup> K/W (19mm), 0.50 m <sup>2</sup> K/W (30 & 35mm) as per EN 12667		
4,4	Humidity resistance	RH95		
++	Clean room	ISO 4 as per ISO 14644-	1	
+	Indoor air quality	A+ E1 IACO		
	Sustainability	43%	BIOSCURIA WOOL  SCIENCIONAL WO	



Distributed by

www.potters.co.nz 0800 POTTERS. | info@potters.co.nz Auckland, Hamilton, Wellington + Christchurch

