




# Rock Face™ ClimaPlus™



Medium textured panel



- Advantages**
- Textured surface with hard core, withstands abuse, temperature and humidity.
  - A fresh, clean look adapts to any interior.
  - When installed in USG's DONN® Band two way exposed grid, it provides an attractive, fast installing, acoustical suspended ceiling at an economical price.
  - FIRECODE™ formulation designed for Fire Resistant ceilings.

- Applications**
- Athletic areas and exercise rooms.
  - Schools
  - Corridors
  - Dormitory rooms
  - Gymnasiums
  - Locker rooms
  - Courthouses
  - Medical Centres

- Grid Options** • DONN® Brand DX® and DXL










Rock Face™ Panels with CLIMAPLUS™ Performance/Donn® Brand DX® Suspension system

# Rock Face™ ClimaPlus™

Acoustical Ceilings

RF/1-05



	Edge Detail	Panel Size <sup>3</sup>	Class	Item No.	NRC <sup>1</sup> Range	CAC <sup>1</sup> Range	Grid Options	Recycled Content	Colour
ROCK FACE™ CLIMAPLUS™ Panels	 (SQ)	1200 x 600 x 15mm		ME56380	.50 - .60	35 - 39	A, B	45%	White
		600 x 600 x 15mm		ME56335	.50 - .60	35 - 39	A, B	45%	White
	<b>A</b> DONN® DX 38D	<b>B</b> DONN® DXL 38D		Retention Clip 20428		Multiclip PPM			
<b>Grid Options</b>			<b>Retaining Clips</b>						

**Installation:** Shall not commence until the building is fully enclosed, watertight, dry, all wet trades (terrazzo, plaster) completed and free of chemical fumes. Do not mix production lots in same ceiling. Environmental conditions are not to exceed 40°C (104°F) and 95% relative humidity.

**Light Fixtures and Fittings:** Shall be independently supported, or load transferred to the grid. Ensure grid loads are within limitations per Loading brochure TLD/1-05.

**Wind uplift:** Use clips to secure panels in regions of high wind conditions.

**Seismic:** Contact your regional USG Ceiling System Specialist.

**Workability:** Easily cut with a Stanley #1991 trimming knife or similar.

**Handling and Storage:** Store flat in a dry location. Handle with care avoiding damage to corners and edges. Do not store on edge or ends. Protect when freighting.

**Cleaning:** Easily cleaned with a soft nozzle vacuum cleaner or a damp cloth or sponge (not wet).

**Short Specification:**

- Ceiling system shall comprise **USG ROCK FACE™ CLIMAPLUS™** abuse resistant, high humidity / fire resistant acoustical ceiling panels in (DONN DX38D 24mm face / DONN DXL38D 24mm face Fire Rated) exposed grid including wall trim as manufactured by USG Interiors.

- Panels shall have NRC .50 - .60, CAC 35 - 39.
- Nominal size 1200mm x 600mm x 15mm
- Edge details shall be Square (SQ).
- Limiting Conditions - Maximum 40°C (104°F) and 95% RH.

**Technical Data**

**Weight:**  
6.25 kg/m<sup>2</sup>

**Recommended Suspension:**  
Donn® DX or Donn® DXL

**Durability tests**  
ASTM C367: Tested to 109 kgf for a 6mm depression by a 50mm steel ball.

**Conditions:**  
Maximum 40°C, 95% RH.

**Light Reflectance (ASTM C523):**  
LR - 1 (Actual .84)

ASTM D1037: Tested to 23 kgf for a 6mm depression by a Janka ball.

**Backloading:**  
None.

**Thermal Resistance (ASTM C177 - 82):**  
R 0.33m<sup>2</sup>°C/W

ASTM D5420: Tested to 0.8 kgf/m for impaction.

**Fire Performance:**

Index	Ignitability	Spread of Flame	Heat Evolved	Smoke Developed
AS1530 3 <sup>2</sup>	0	0	0	2
ASTM E84	-	25	-	10

**Footnotes**

**1. Acoustic Test Standards**  
NRC to ASTM C423  
CAC to ASTM E1414

**2. Test Report:** Works Consultancy Services  
93-27902.88 - full copy available on request

**3. Class A** - regular formulation  
 - Firecode formulation

**4. Imperial Panel** sizes available. Contact your USG Ceiling Systems Specialist.

**Safety First!**

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.

**Distributor:**



\*Warranty covers USG acoustical ceiling panel and USG DONN® Brand grid systems against defects in material or manufacturing workmanship for the useful life of the ceiling system, up to a maximum of 30 years. See your regional USG Ceiling Systems Specialist for full warranty details.